

FPD4-80-1000-30


4-Way, 0.08~1GHz

Features:

- * Small Size
- * Low Insertion Loss

Applications:

- * Laboratory Test
- * Telecommunication
- * Wireless
- * Instrumentation



Electrical

Frequency:	0.08~1GHz
Insertion Loss ^{*1} :	2.4dB max.
Input VSWR:	1.35 max.
Output VSWR:	1.15 max.
Isolation:	20dB min.
Amplitude Balance:	±0.1dB typ.
Phase Balance:	±1° typ.
Impedance:	50Ω
Power @SUM Port:	30W max. as divider 2W max. as combiner

[1] Excluding theoretical loss 6dB.

Mechanical

Connectors:	SMA Female, N Female
Mounting:	4-Φ3.2mm through-hole

Environmental

Operating Temperature:	-45~+85°C
Non-operating Temperature:	-55~+125°C

How To Order

FPD4-80-1000-30-Y

Y: Connector type

Connector naming rules:

S - SMA Female (Outline A)



N - N Female (Outline B)

Examples:

To order a 4-way power divider, 0.08~1GHz, 30W, N female, specify FPD4-80-1000-30-N.

Customization is available upon request.


Outline Drawings




Unit: mm [in] Tolerance: ±0.5mm [±0.02in]

Typical Performance Curves


Input VSWR vs. Frequency




Output VSWR vs. Frequency




Insertion Loss vs. Frequency



Isolation vs. Frequency



Amplitude Balance vs. Frequency



Phase Balance vs. Frequency

