

## FBC-13750-14500-70-42S

Ku-Band, 13.75~14.5GHz, 70dB, 16W (42dBm)

**Features:**

- \* Low Power Consumption
- \* High Power Threshold Setting
- \* Fully Modular Design
- \* Integrated Structural Design

**Applications:**

- \* Satellite Earth Station
- \* Satellite Communication
- \* Telecommunication

**Electrical**

---

RF Frequency:	13.75~14.5GHz
IF Frequency:	950~1700MHz
Output Power (Psat):	16W (42dBm)
Power Consumption:	70W typ. @Prated
Small Signal Gain:	70dB
Gain Flatness:	3dB/500MHz, 4dB/750MHz max.
Gain Stability:	3dB max.
IM3:	-25dBc
Spurious:	-55dBc
Input/Output VSWR:	1.5/2.0
Phase Noise:	-75dBc/Hz@1KHz -85dBc/Hz@10KHz -95dBc/Hz@100KHz
External Reference:	10MHz, 0±5dBm
Supply Voltage:	+18~+55VDC
Impedance:	50Ω

**Environmental**

---

Operating Temperature:	-40~+60°C
Operating Humidity:	0~100% (Condensing)

**Mechanical**

---

IF, Ext.ref. input connector:	50Ω N Female/75Ω F Inch Thread Female
Output Waveguide Size:	WR-75 (BJ120)
Monitor:	PT02E-14-12P
Weight:	1Kg

[1] Exclude connectors.

**Outline Drawings**

To be done.

Unit: mm [in]

Tolerance: ±0.5mm [±0.02in]

**How To Order**

**FBC-13750-14500-70-42S-X**

X: Input connector type

Connector naming rules:

N - N female

F - F Inch Thread female

Examples:

To order a Block Up Converter (BUC), 13.75~14.5GHz, 70dB, 16W (42dBm), N female, specify FBC-13750-14500-70-42S-N.

Customization is available upon request.