

## FAA1Y 1-5/8" (IF70) to HN

Features:  
\* Low VSWR

Applications:  
\* Wireless  
\* Transmitter  
\* Laboratory Test  
\* Radar

### Electrical

Frequency:	DC~3GHz
VSWR:	1.1@DC~1000MHz max.
Dielectric Withstanding Voltage:	6000V RMS, 50Hz, at sea level, min.
Working Voltage:	2100V RMS, 50Hz, at sea level, max.
Impedance of Dielectric:	5000MΩ min.
Average Power:	3.4KW@900MHz
Peak Power:	20KW max.
Impedance:	50Ω

### Mechanical

RF Connectors:	1-5/8" (IF70) HN
Mating Life Cycle:	100 cycles min.
ROHS Compliant:	Full ROHS compliance
Outer Conductor:	Nickel plated brass
Dielectric:	PTFE
Inner Conductor:	Silver plated brass
Gasket:	Silicone rubber
Waterproof:	With O-Ring

### Environmental

Temperature:	-55~+85°C
--------------	-----------


### How To Order

**FAA1Y-M** - 1-5/8" to HN (m), Outline A


**FAA1Y-F** - 1-5/8" to HN (f), Outline B

Customization is available upon request.

### Outline Drawings



Outline A



Outline B

Unit: mm [in]

Tolerance: ±0.2mm [±0.008in]