

FDA-10-50000-63.5-0.5


10MHz~50GHz, 63.5dB, 0.5dB

Features:

- * Broadband
- * High Dynamic Range

Applications:

- * Laboratory Test
- * Telecommunication
- * Wireless
- * Instrumentation



Electrical

Frequency:	10MHz~50GHz
Insertion Loss:	13dB typ.
Step:	0.5dB
Attenuation Range:	0~63.5dB
Attenuation Accuracy:	±3.5dB typ.
VSWR:	2.2 typ.
Voltage/Current:	-5V @15mA typ.
Switching Time:	20ns typ.
Logic Input:	On: 1(+2.3~+5V) Off: 0(0~+0.8V)

Absolute Maximum Ratings*1

Input Power:	+24dBm
Voltage:	+6V

[1] Permanent damage may occur if any of these limits are exceeded.

Mechanical

Size*2:	36*26*12mm 1.417*1.024*0.472in
RF Connectors:	2.4 Female (Removable)
Power Supply & Control Interface Connectors:	J30J-9ZKP
Mounting:	4-Φ2.8mm through-hole

[2] Exclude connectors.


Pin Numbering

Pin	Function	Pin	Function
1	C1:-0.5dB	6	C6:-16dB
2	C2:-1dB	7	C7:-32dB
3	C3:-2dB	8	VEE
4	C4:-4dB	9	GND
5	C5:-8dB		

Environmental

Operating Temperature:	-45~+85°C
Non-operating Temperature:	-55~+125°C

Outline Drawings



Unit: mm [in]

Tolerance: ±0.5mm [±0.02in]

Logic Table

State	C1	C2	C3	C4	C5	C6	C7	VEE	Attenuation State
-	0	0	0	0	0	0	0	-5V	Reference IL
1	1	0	0	0	0	0	0	-5V	0.5dB
2	0	1	0	0	0	0	0	-5V	1dB
3	0	0	1	0	0	0	0	-5V	2dB
4	0	0	0	1	0	0	0	-5V	4dB
5	0	0	0	0	1	0	0	-5V	8dB
6	0	0	0	0	0	1	0	-5V	16dB
7	0	0	0	0	0	0	1	-5V	32dB
8	1	1	1	1	1	1	1	-5V	63.5dB

How To Order

FDA-10-50000-63.5-0.5

Customization is available upon request.

Typical Performance Curves

